



P-22065

HYDRAULIC RECOVERY KIT H2

Web version manual

For complete version
contact Bygging-Uddemann:
info@bygging-uddemann.se



TABLE OF CONTENTS

- 1. Brief Specification**
- 2. How to Use**
- 3. How to Maintain and Service**
- 4. Part List**



1. **BRIEF SPECIFICATION**

1.1 **Feature**

Centerhole hydraulic jack fitted between gripping devices. These gripping devices are trailing in one direction and locking in the reverse. The grippers comprise of a pair of tilting dice, which are forced by springs against the climb tube. Locking one way is caused by means of curved edges. Our design is based for a rapid reclaim of climb tubes/rods before stripping out a slipform commences. Drawing No 1D-2513 shows parts for alternative yokes.

1.2	Weight	Approx 35 kgs
1.3	Stroke	100 mm
1.4	Displacement volume	0,3 litre per stroke
1.5	Piston area	18,8 cm²
1.6	Retract area	10,2 cm²
1.7	Max work pressure	150 bar
1.8	Manufacturing test pressure	200 bar
1.9	Centerhole	35 mm
1.10	Options	
	Tube	dia 27 mm dice stamped " 3"
	Tube/rod	dia 32 mm dice stamped " 6"
	Tube	dia 33,7 mm dice stamped "34"

Force at 110 bar = 2 tons.



Web version manual

For complete version
contact Bygging-Uddemann:
info@bygging-uddemann.se